

BEKOATAŞ SUPER LUX CHLORINATED RUBBER COLD ROAD - LINE PAINT



Floor

Solvent

Application Recommendation

Application Areas

- Can be used safely all types of wood and metal surfaces with primers.
- Dries quickly and abrasion-resistant
- High adhesion strength, dry quickly, high-performance matt paint.
- Used as road line marking, painting curbs, used car park marking

Equipment



Zuben Super Lux
Line Paint

Equipment



Scraper

Gypsumtrowel

Puttyshovel

Spatula

Trowel

Dust Cloth

Brush

Mixer

Adjustable
Stick

Paint Bucket

Surface Preparation

- Before the application, surface should be cleaned from all the dust, dirt and hard core etc.
- Lacking and broken parts on pavements should be fixed or changed.
- Shouldn't be applied on limp or decayed surfaces.
- According to the application tool, Zuben Line Paint may need to be thinned with a thinner between %0-10.



BEKOTAŞ SUPER LUX CHLORINATED RUBBER COLD ROAD - LINE PAINT



Floor

Solvent

Product Code: 455

Product Description

- High adhesion strength, dry quickly, high-performance matt paint.

Application Areas

- Can be used as road line marking, painting curbs, used car park marking.

Advantages

- Dries quickly.
- Friction-resistant.



Matt



Brush



Roll



Spray Pistolet

Technical specifications:

Structure

- Alkyd resin based, Solvent based

Diluting

- Toluene

Appearance on the packing

- Dark, Stable, Jelly

Dry Appearance

- Matt, Pastel, Smooth

Color

- White, Yellow, Orange

Water Vapor Permeability

- SD (m) (TS EN ISO 7783-2):
Approximately: 30

Drying Time

- (between +5 +35 °C) starting time to second layer is 2 hours, completely drying time 6 hours. Lower temperature and high relative humidity lengthens the drying time.

Coverage

- Depending on the surface smoothness and absorbency approximately 5-7 m²/lt. per a layer.

Shelf Life

- In package and in 5-35 °C 2 years

Packing

- 20 kg tin bucket.

Safety Recommendations

- S2: Keep out the reach of children.
- S24/25: Avoid contact with eyes and skin.
- S26: In case of contact with eyes immediately wash with water and contact with a doctor.
- S28: In case of contact with skin immediately wash with water.
- S29: Do not discharge into drains or water courses.
- S46: If swallowed, seek medical advice immediately and show the container or label. Mix before using. Close the cover after using. Protect from frost and direct sunlight.

Quality Certificate

- TS 5808
Public exposure No. 04.524/604.506/E3

