

GOLD VARNISH WOOD PROTECTOR



Exterior

Interior
Wall

Solvent

Application Recommendations

Application Areas

- It use wooden house, window, balcony, exterior and interior door, wooden fence, columns and beams, furniture components and similar surfaces.

Equipment



Gold Varnish
Wood Protector

Equipment



Surface Preparation



- Application surfaces must cleaned from every dirt, rust and oil.
- Old painted surfaces must be cleaned completely.
- Must be removed dirt and new resin on the wood surfaces to be painted.
- Before application Gold Varnish Wood Protector must be mix.
- Gold Varnish Wood Protector must be application twice by roller, brush or spray gun.
- Temperature should be between 5 ° C-30 ° C during application.

Application



During application and during the subsequent 24 hours at the ambient temperature of the surface should be +5 ° C.



Before application Gold Transparent Wood Protector should be mixed.



Gold Transparent Wood Protector thinned with clean water 10% and application for two layer by brush, roller or spray.



Should be waited minimum 6 hours between layers.

After Application

Application tools should be washed with water after use immediately.

GOLD VARNISH WOOD PROTECTOR



Exterior

Interior

Solvent

Product Code: 305

Product Description

- ◆ Modified alkyd resin with high penetration power, lead-free, ready to use, bright, decorative wood preservative.

Application Areas

- ◆ It use wooden house, window, balcony, exterior and interior door, wooden fence, columns and beams, furniture components and similar surfaces. Should not be used beehives wood

Advantages

- ◆ Extends the life of the applied material.
- ◆ It penetrates deep into the wood with high penetration power.
- ◆ Wood is protective against harmful insects and corky.
- ◆ Corrosive resistant to UV rays, color fade and does not cover the wood's natural appearance.
- ◆ Short drying time, moisture is capable of adjusting and excellent workability.



Bright



Brush



Roll



Spray Pistle

Technical specifications:

Structure

- ◆ Alkyd resin based, Solvent based

Diluting

- ◆ Solvent

Appearance on the packing

- ◆ Dark, Stable, Jelly

Dry Appearance

- ◆ Bright, Smooth.

Color

- ◆ Transparant and any colour in colour chart

Water. Vaporpermeability

- ◆ SD (m) (TS EN ISO 7783-2):
Approximately: 80

Drying Time

- ◆ (between +5 +35 °C) Touching time: 3 hours Doesn't hold dust for 8 hours. Complete drying time: 24 hours. Lower temperature or high relative humidity lenghtens the drying time.

Coverage

- ◆ Depending on the surface smoothness and absorbency approximately 10-12 m²/lt.



Shelf Life

- ◆ In package and in 5-35 °C 2 years

Packing

- ◆ 12 - 2,5 and 0.75 tin bucket.

Safety Recommendations

- ◆ S2: Keep out the reach of children.
- ◆ S24/25: Avoid contact with eyes and skin.
- ◆ S26: In case of contact with eyes immediately wash with water and contact with a doctor.
- ◆ S28: In case of contact with skin immediately wash with water.
- ◆ S29: Do not discharge into drains or water courses.
- ◆ S46: If swallowed, seek medical advice immediately and show the container or label. Mix before using. Close the cover after using. Protect from frost and direct sunlight.

Quality Certificate

- ◆  TS 5808
Public exposure No. 04.524/604.506/E3