

GOLD YACHT VARNISH



Exterior

Interior
Wall

Solvent

Application Recommendations

Application Areas

- It is use on the sea vehicles and wooden of interior and exterior surfaces for decorative and protective purposed.

Equipment



Gold
Yacht Varnish

Equipment



Scraper

Gysumtrowel

Puttyshovel

Spatula

Trowel

Dust Cloth

Brush

Mixer

Adjustable
Stick

Paint Bucket

Surface Preparation



Mortar



Concrete



Cement Board



Gypsum Panels



Old Plastic Paint



Plaster Board



Glasstextile



Wallpaper

- Golden Yacht varnish to be applied wood surfaces must be free of contaminants such as oil and swollen remains.

- Wood against mold and fungus for many years is recommended to use wood impregnated for protection. It is recommended that if this is not possible, practical implementation of impregnation.

- Gold Yacht varnish, application with spray gun by dilution 10 to 20%, with brush and roller application dilution 5-10% with synthetic thinner, 3 times in one day with sanded between coats should be applied.

- Application tools should be cleaned immediately after use with synthetic thinner.

- Temperature should be between 5 ° C-30 ° C during application.

Application



During application and during the subsequent 24 hours at the ambient temperature of the surface should be +5 ° C.



Before application Gold Yacht Varnish should be mixed.



Gold Yacht Varnish thinned with clean water 10% and application for two layer by brush, roller or spray.



Should be waited minimum 6 hours between layers.

After Application

Application tools should be washed with water after use immediately.

GOLD YACHT VARNISH

BEKOTAŞ
Boya

Exterior

Interior

Solvent

Product Code: 310

Product Description

- ◆ Based urethane alkyd resin combination, lead-free yacht varnish forms a perfect high gloss surface.

Application Areas

- ◆ It is used on the sea vehicles and wooden of interior and exterior surfaces for decorative and protective purposes.

Advantages

- ◆ Has high brightness.
- ◆ Transparent color.
- ◆ It does not contain lead.
- ◆ Resistant to UV.
- ◆ Perfectly protects the wood against variable atmospheric conditions.



Bright



Brush



Roll



Spray Pistolet

Technical specifications:

Structure

- ◆ Alkyd resin based, Solvent based

Diluting

- ◆ Solvent

Appearance on the packing

- ◆ dark, stable, jelly

Dry Appearance

- ◆ bright, smooth.

Color

- ◆ transparent and any colour in colour chart

Water. Vaporpermeability

- ◆ SD (m) (TS EN ISO 7783-2):
Approximately: 80

Drying Time

- ◆ (between +5 +35 °C) Touching time: 3 hours
Doesn't hold dust for 8 hours.
Complete drying time: 24 hours.
Lower temperature or high relative humidity lengthens the drying time.

Coverage

- ◆ Depending on the surface smoothness and absorbency approximately 10-12 m²/lt.

Shelf Life

- ◆ In package and in 5-35 °C 2 years

Packing

- ◆ 12 kg tin bucket.

Safety Recommendations

- ◆ S2: Keep out the reach of children.
- ◆ S24/25: Avoid contact with eyes and skin.
- ◆ S26: In case of contact with eyes immediately wash with water and contact with a doctor.
- ◆ S28: In case of contact with skin immediately wash with water.
- ◆ S29: Do not discharge into drains or water courses.
- ◆ S46: If swallowed, seek medical advice immediately and show the container or label.
- ◆ Mix before using. Close the cover after using.
- ◆ Protect from frost and direct sunlight.

Quality Certificate

- ◆  TS 5808
Public exposure No. 04.524/604.506/E3

