

GOLD SYNTHETIC ANTIRUST PAINT



Application Recommendations

Application Areas

- Can be used safely with appropriate undercoat with on wood, iron-steel, cement, concrete, plaster, cement board, gypsum board, OSB, MDF interior and exterior surfaces.

Equipment



Gold Synthetic Undercoat Paint



Gold Synthetic Anti-Rust Paint

Equipment



Scraper

Gypsum trowel

Puttyshovel

Spatula

Trowel

Dust Cloth

Brush

Mixer

Adjustable Stick

Paint Bucket

Surface Preparation



Mortar



Concrete



Cement Board



Gypsum Panels



Old Plastic Paint



Plaster Board



Glasstextile



Wallpaper

• Application surfaces must be removed from oil, dirt, rust and blistered paint.

• Should be made absolutely sanders before old painted wall and wooden surfaces before application, surfaces must be cleaned and priming with Gold synthetic Antirust Paint .Old Painted and metal surface must be free from rust with sandpaper.If not signs of rust surface should be priming with synthetic undercoat and should then be painted with Gold synthetic Antirust Paint Topcoat after correction surface with fine sandpaper.

• New wood surfaces to be painted surfaces must be primed with Gold synthetic Antirust Paint after saturating the wood preservative.Should be applied twice Gold Antirust new painted and iron-steel surfaces.

• Gold Lux Synthetic Antirust Paint roller,brush or spray application

to bring consistency must be thoroughly mixed with the synthetic thinner thinned 5-10%.


• Gold synthetic Antirust Paint Topcoat applied sanded prepared surfaces after 24 hours by brush,roller,or spray gun.Must be waited 1 day between layer application.

• Airless spray pressure of 120-140 bar, nozzle angle 50 °, size should be 0.013 inches.

• Application tools must cleaned with thinner after application.

• Temperature should be between 5 ° C-30 ° C during the application.

Application



During application and during the subsequent 24 hours at the ambient temperature of the surface should be +5 ° C.



Before application Gold Synthetic Antirust Paint should be mixed.



Gold Synthetic Antirust Paint thinned with clean water 10% and application for two layer by brush, roller or spray.



Should be waited minimum 6 hours between layers.

After Application

Application tools should be washed with water after use immediately.

GOLD SYNTHETIC ANTIRUST PAINT

BEKOTAŞ
Boya

Exterior

Interior

Solvent

Product Code: 270

Product Description

- ◆ It has superior cover power, unleaded, Synthetic alkyd resin primer.

Application Areas

- ◆ Can apply to iron surfaces interior and exteriors.

Advantages

- ◆ It has superior cover power
- ◆ With a special combination of alkyd anticorrosive pigments in anticorrosive and iron structure
- ◆ protects surfaces against corrosion.
- ◆ Excellent adhesion to the surface applied.
- ◆ Creating a smooth and sturdy surface finish makes it available to the application surface.
- ◆ It does not contain lead.



Bright



Brush



Roll



Spray Pistol

Technical specifications:

Structure

- ◆ Alkyd resin based, Solvent based

Diluting

- ◆ Solvent

Appearance on the packing

- ◆ Dark, Stable, Jelly

Dry Appearance

- ◆ Matt, Pastel, Smooth

Color

- ◆ White, Grey, Red

Water Vapor permeability

- ◆ SD (m) (TS EN ISO 7783-2):
Approximately: 150

Drying Time

- ◆ (between +5 +35 °C)
Touching time: 3 hours Doesn't hold dust for 8 hours. Complete drying time: 24 hours. Lower temperature or high relative humidity lengthens the drying time.

Coverage

- ◆ Depending on the surface smoothness and absorbency approximately 7,5-9 m²/lt. per a layer.

Shelf Life

- ◆ In package and in 5-35 °C 2 years

Packing

- ◆ 20 - 3 and 1 kg tin bucket.

Safety Recommendations

- ◆ S2: Keep out the reach of children.
- ◆ S24/25: Avoid contact with eyes and skin.
- ◆ S26: In case of contact with eyes immediately wash with water and contact with a doctor.
- ◆ S28: In case of contact with skin immediately wash with water.
- ◆ S29: Do not discharge into drains or water courses.
- ◆ S46: If swallowed, seek medical advice immediately and show the container or label. Mix before using. Close the cover after using. Protect from frost and direct sunlight.

Quality Certificate

- ◆  TS 5808
Public exposure No. 04.524/604.506/E3

